

RONELO



- High efficiency deep reflector with clear cover glass.
- Supplied with non-dimmable drivers as standard.
- Dimmable options.
- Increased efficiency
- 2-3 SDCM
- L90/B10 50.000h


Preliminary Data



LIGHTSOURCE BY
bridgelux

Model (LED Power)	Colour Temperature*	LED Lumen	CRI***	Type	Beam Angle	Colour	Dimming Option	Accessories
RONELO 45.2W (RONELO 45)	(27B7001)	2700K - 7001lm	(80) 80	(AD) Adjustable	(20) 20° (38) 38° (60) 60° (110) 110°	(WH) White	(00) Without Driver (ND) Non Dimmable (A1) Analogue (1-10V) (DL) DALI (PB) Push Button (WL) Wireless **	COVER (0X) Standard (1X) Diffuser (2X) Frosted Center ↓ (XX) EXTRAS (X0) No Extras
	(30B7438)	3000K - 7438lm						
	(40B7657)	4000K - 7657lm						
	(57B7438)	5700K - 7438lm						
RONELO 53.3W (RONELO 53)	(27B8068)	2700K - 8068lm						
	(30B8572)	3000K - 8572lm						
	(40B8824)	4000K - 8824lm						
	(57B8572)	5700K - 8572lm						
RONELO 61.5W (RONELO 62)	(27B9112)	2700K - 9112lm						
	(30B9682)	3000K - 9682lm						
	(40B9967)	4000K - 9967lm						
	(57B9682)	5700K - 9682lm						
RONELO 45.2W (RONELO 45)	(27B5776)	2700K - 5776lm	(90) 90					
	(30B6038)	3000K - 6038lm						
	(40B6388)	4000K - 6388lm						
RONELO 53.3W (RONELO 53)	(27B6656)	2700K - 6656lm						
	(30B6958)	3000K - 6958lm						
	(40B7362)	4000K - 7362lm						
RONELO 61.5W (RONELO 62)	(27B7518)	2700K - 7518lm						
	(30B7859)	3000K - 7859lm						
	(40B8315)	4000K - 8315lm						

* Models with CCTs of 3500K, 5000K & 6500K are available upon request.
 ** The wireless dimming option includes driver and Bluetooth dimming accessory.
 ***CRI90 Available up to 5000K. CRI97 Available upon request.



Ordering Code Example:
 RONELO 53-40B8824-80-AD-60-WH-ND-00